



# AMTEQ<sup>®</sup>

B o h r z u b e h ö r G m b H

### Performance Data

Liner size, inches (mm)		9**** (228.6)	8" (203.2)	7-1/2" (190.5)	7" (177.8)	6-1/2" (165.1)	6" (152.4)	5-1/2" (139.7)	5" (127)	
Max. Discharge Pressure, psi (kg/cm2) with high pressure Fluid End***		2795 (196.5)	3535 (248.6)	4025 (283.0)	4615 (324.5)	5360 (376.8)	6285 (441.9)	7475 (525.5)	7500 (527.3)	
Pump Speed spm	Input HP, HP (kW)	Hyd.** HP, HP (kW)	GPM** (LPM**)	GPM** (LPM**)	GPM** (LPM**)	GPM** (LPM**)	GPM** (LPM**)	GPM** (LPM**)	GPM** (LPM**)	
105*	2200* (1641*)	1980 (1476)	1215 (4600)	960 (3634)	843 (3191)	735 (2782)	633 (2396)	540 (2044)	454 (1718)	
80	1676 (1250)	1509 (1125)	925 (3501)	731 (2767)	643 (2434)	560 (2120)	483 (1828)	411 (1556)	346 (1309)	
60	1257 (937)	1131 (843)	694 (2627)	548 (2074)	482 (1824)	420 (1590)	362 (1370)	308 (1166)	259 (980)	
40	838 (625)	754 (562)	462 (1748)	366 (1385)	321 (1215)	280 (1060)	241 (912)	206 (780)	173 (654)	
Volume/Stroke, gal. (Liters)		11.57 (43.797)	9.14 (34.598)	8.03 (30.397)	7.00 (26.498)	6.03 (22.826)	5.14 (19.457)	4.32 (16.353)	3.57 (13.514)	
*Rated maximum input horsepower and speed					****5,000 PSI Fluid End configuration available					
**Based on 90% mechanical efficiency and 100% volumetric efficiency					**** 9-inch liner requires special liner bushing and liner clamp					

