

Leistungsdaten

Performance Chart

Oilwell A-1700-PT, 7.1/2" X 12"

Zylinder I.D. in Zoll Liner diameter in inch	7"	6 1/2"	6"	5 1/2"	5 "
max. Betriebsdruck in Bar / <i>max. Discharge Pressure psi</i>	200 2915	233 3381	274 3968	325 4723	345 5000
max. Liter pro Umdrehung / <i>Volume per Stroke in US-Gallons</i>	22,70 6,00	19,58 5,17	16,68 4,40	14,00 3,70	11,58 3,06
Drehzahl der Pumpe in U/min <i>Pump Speed rpm</i>	Fördermenge der Pumpe in Liter / Minute Gallons / min				
	Discharge Flow US-				
20	454 120	392 103	334 88	280 74	231 61
30	681 180	587 155	500 132	420 111	347 92
40	908 240	783 207	667 176	560 148	463 122
50	1135 300	979 258	834 220	701 185	579 153
60	1362 360	1175 310	1001 264	840 222	695 184
70	1589 420	1371 362	1168 308	980 259	811 214
80	1816 480	1566 414	1334 352	1120 296	926 245
90	2043 540	1762 465	1501 396	1260 333	1042 275
100	2270 600	1958 517	1668 441	1400 370	1158 306
110	2497 660	2153 569	1835 484	1540 407	1274 337
120	2724 720	2349 620	2002 529	1680 444	1390 367

Based on vol. efficiency 100%
mech. efficiency 90%

HP= Horse Power(1HP=0,746kW)
Gear Ratio= 4,5:1

SAP-Equipment Nr.

Inventar Nr.

Transportmaße:
Dimension

LxBxH, 8300 x 3400 x 3200 mm

Transportgewicht:
Weight

37 to